

# PTE1500

## Portable Electric Oil-Free Screw Compressor: PTE1500



### General Information

Dimensions LxWxH (mm)	5440 x 2210 x 2350
Mass (Wet - Ready to operate) (kg)	6850
Discharge Outlet	80mm Evertite 3" Male Spud with Gasket
Sound Pressure Level (7m) dB (A)	98

### Engine

Cummins QSX15

Power (kW)	300/400
Voltage (V)	400
Frequency (Hz)	50
Start Up Amps (A)	1200
Running Amps @ 7-10 bar (A)	500-560
Circuit Breaker (A)	630
Cabling	2 x 120mm

### Performance

#### Capacity (Free Air Delivery)

Working Pressure	cfm	m³/min	l/s
Pressure up to 6,9 bar (g)	1613	45,7	792
Pressure up to 9,3 bar (g)	1522	43,1	718
Pressure up to 10,3 bar (g)	1320	37,4	623

### Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Spillage Free Frame
Hot Air Outlet	Integrated Aftercooler + Water Separator	Fork Lift Slots & Lifting Eye
Strobe light Indicating Unit is operational	Class Zero Certified (Oil-Free Acc to ISI8573-1)	SANS Government Approved Safety Relieve Valve and Vessel Certificate

### Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com

For Information Only. Subject to change without notice. Information is for guidance only contact your nearest rental office for application advice .

2021-11-18