

GA22+ & GA22FF



Electric Driven Oil-Injected Screw Compressor: Various GA22 Models



Machine may not look as it appears

General Information		GA22+	GA22FF
Dimensions LxWxH (mm)		1267 x 790 x 1590	780 x 811 x 1590
Mass (Wet - Ready to operate) (kg)		363	485
Discharge Outlet		3/4 " Chicago Claw Coupling with Gaskets	3/4 " Chicago Claw Coupling with Gaskets
Sound Pressure Level (7m) dB (A)		67	67
Engine		GA22+	GA22FF
Main Electric Motor Power (kW)		22	22
Voltage (V)		400V	400V
Frequency (Hz)		50	50
Start Up Amps (A)		160 A	160 A
Full Load Running Amps @ 7-10 bar (A)		65 A	65 A
Supply Circuit Breaker (A)		100 A	100 A
Electric Supply Cabling		16mm	16mm
Performance		Capacity (Free Air Delivery)	
Working Pressure	cfm	m ³ /min	l/s
Pressure up to 7,5 bar(g)	140-154	3,9-4,4	66-72
Other features			
Emergency Stop Switch	Reliable Motor & Drive Train	Fork Lift Slots	
Robust & Silent	Water Separator	Elektronikon Touch Display	
Fitted with Phase Protection Relay	Integrated Aftercooler (Certain Fleet Models only)	SANS Government Approved Safety Relieve Valve and Vessel Certificate	

Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com

For Information Only. Subject to change without notice. Information is for guidance only contact your nearest rental office for application advice .

2021-11-17